

CECW-EH-D

Manual
No. 1110-2-1418

31 October 1994

**Engineering and Design
CHANNEL STABILITY ASSESSMENT FOR
FLOOD CONTROL PROJECTS**

Table of Contents

| Subject | Paragraph | Page | Subject | Paragraph | Page |
|--|-----------|------|--|-----------|------|
| Chapter 1 | | | Chapter 3 | | |
| Introduction | | | Stability Problems with Flood Control Channels | | |
| Purpose | 1-1 | 1-1 | <i>Section I</i> | | |
| Applicability | 1-2 | 1-1 | <i>Types of Channel Modification for Flood Control</i> | | |
| References | 1-3 | 1-1 | General | 3-1 | 3-1 |
| Explanation of Terms | 1-4 | 1-1 | Clearing and Snagging | 3-2 | 3-1 |
| General Approach | 1-5 | 1-1 | Cleanout | 3-3 | 3-1 |
| Discussion | 1-6 | 1-1 | Enlargement | 3-4 | 3-2 |
| Systematic Approach to Channel Stability | 1-7 | 1-1 | Realignment | 3-5 | 3-2 |
| Chapter 2 | | | Levees | 3-6 | 3-2 |
| Channel Stability Principles | | | Flood Bypass Channels | 3-7 | 3-4 |
| <i>Section I</i> | | | Flow Diversions | 3-8 | 3-5 |
| <i>Characteristics of Channels in Erodible Materials</i> | | | <i>Section II</i> | | |
| Geomorphic Context | 2-1 | 2-1 | <i>Case Examples of Stability Problems</i> | | |
| Common Channel Types | 2-2 | 2-2 | Twenty Mile Creek | 3-9 | 3-5 |
| Channel Geometry and Processes | 2-3 | 2-5 | Puerco River | 3-10 | 3-5 |
| <i>Section II</i> | | | Grapevine Spillway Channel ... | 3-11 | 3-7 |
| <i>Principles of Channel Equilibrium and Response</i> | | | Snake River | 3-12 | 3-8 |
| Basic Concepts | 2-4 | 2-9 | Little Tallahatchie River | 3-13 | 3-8 |
| Applicability to Flood Control Projects | 2-5 | 2-11 | Red River | 3-14 | 3-9 |
| Response of Channels to Altered Conditions | 2-6 | 2-13 | Sacramento River | 3-15 | 3-10 |
| Channel Evolution and Geomorphic Thresholds | 2-7 | 2-15 | Long Creek Basin | 3-16 | 3-10 |
| | | | Tanana River | 3-17 | 3-11 |

| Subject | Paragraph | Page |
|--|-----------|------|
| <i>Section III</i> | | |
| <i>Causes and Forms of Instability</i> | | |
| General | 3-18 | 3-12 |
| Continuation of Pre-existing Processes, e.g., Meandering | 3-19 | 3-12 |
| Increased Discharges | 3-20 | 3-15 |
| Realignment and Channel Improvement | 3-21 | 3-15 |
| Flow Regulation by Reservoirs | 3-22 | 3-15 |
| Sediment Transport and Channel Stability | 3-23 | 3-16 |
| Chapter 4 | | |
| Assembly of Information for Stability Evaluation | | |
| General | 4-1 | 4-1 |
| Review of Historical Developments | 4-2 | 4-1 |
| Map and Aerial Photo Interpretation | 4-3 | 4-2 |
| Field Inspection | 4-4 | 4-2 |
| Key Points and Features | 4-5 | 4-3 |
| Channel and Floodplain Surveys | 4-6 | 4-8 |
| Streamflow and Related Data | 4-7 | 4-10 |
| Geologic and Geotechnical Information | 4-8 | 4-11 |
| Sediment Transport | 4-9 | 4-12 |
| Chapter 5 | | |
| Evaluation of Stability | | |
| General | 5-1 | 5-1 |
| Levels of Detail | 5-2 | 5-1 |
| Technical Approaches and Their Application | 5-3 | 5-1 |
| Allowable Velocity and Shear Stress | 5-4 | 5-2 |
| Empirical Relationships for Channel Properties | 5-5 | 5-7 |
| Analytical Relationships for Channel Properties | 5-6 | 5-7 |
| Sediment Transport and Sediment Budget | 5-7 | 5-10 |

| Subject | Paragraph | Page |
|--|-----------|------|
| Slope Stability | 5-8 | 5-13 |
| Meander Geometry | 5-9 | 5-13 |
| Basinwide Evaluation for System Rehabilitation | 5-10 | 5-14 |
| General Stepwise Approach | 5-11 | 5-16 |
| Checklist of Items to Consider | 5-12 | 5-16 |
| Example of Qualitative Evaluation | 5-13 | 5-18 |

Chapter 6
Practical Aspects of Stability Design

| | | |
|---|------|------|
| General | 6-1 | 6-1 |
| Ranking of Flood Control Methods | 6-2 | 6-1 |
| Alignment and Planform | 6-3 | 6-1 |
| Single-Channel Streams | 6-4 | 6-1 |
| Multichannel Streams | 6-5 | 6-3 |
| Alluvial Fans | 6-6 | 6-3 |
| Longitudinal Profile and Grade Controls | 6-7 | 6-5 |
| Cross Sections and Hydraulic Capacities | 6-8 | 6-8 |
| Control of Meandering | 6-9 | 6-13 |
| Bank Protection | 6-10 | 6-14 |
| Control of Sediment Deposition | 6-11 | 6-15 |

Appendix A
References

Appendix B
Basis of Certain Charts in Paragraphs 5-4 and 5-5

Appendix C
Examples of Quantitative Stability Evaluation

Appendix D
Notation

List of Figures

| Figure | Page | Figure | Page |
|--|------|---|------|
| 1-1 | 1-2 | 2-28 | 2-20 |
| Flowchart for systematic approach to channel stability | | Undercut bank erosion in frozen fine-grained alluvium (Kuskokwim River, Alaska) | |
| 2-1 | 2-1 | 3-1 | 3-1 |
| Drainage basin zones and some channel types | | 3-2 | 3-2 |
| 2-2 | 2-1 | Channel enlargement | |
| Typical longitudinal stream profile and direction of change through time | | 3-3 | 3-3 |
| 2-3 | 2-3 | Channel enlargement by side berm cut | |
| Mountain torrent | | 3-4 | 3-3 |
| 2-4 | 2-3 | Forms of channel realignment | |
| Alluvial fan | | 3-5 | 3-3 |
| 2-5 | 2-3 | Realigned channel without serious instability problems | |
| Braided river | | 3-6 | 3-3 |
| 2-6 | 2-3 | Lateral instability in realigned channel | |
| Arroyo | | 3-7 | 3-4 |
| 2-7 | 2-4 | Effects of levees on flood hydrographs | |
| Meandering alluvial river | | 3-8 | 3-4 |
| 2-8 | 2-5 | Bank protection necessitated by encroachment on levee setback | |
| Incised channel | | 3-9 | 3-4 |
| 2-9 | 2-5 | Flood bypass channel formed by high-level bend cutoffs | |
| Regulated river | | 3-10 | 3-6 |
| 2-10 | 2-5 | Cross-section and profile responses to channel enlargement, Twenty Mile Creek | |
| Delta | | 3-11 | 3-7 |
| 2-11 | 2-7 | Induced instability upstream of channel enlargement, Twenty Mile Creek | |
| Some forms of stream planform | | 3-12 | 3-7 |
| 2-12 | 2-8 | Entrenched reach of Puerco River | |
| Channel classification based on pattern and type of sediment load | | 3-13 | 3-7 |
| 2-13 | 2-8 | Grapevine Spillway Channel after erosional episode | |
| Examples of meander shifting and bank erosion | | 3-14 | 3-8 |
| 2-14 | 2-8 | Snake River near Jackson Hole | |
| Mechanisms of cross-sectional adjustment to altered inputs of water and sediment | | 3-15 | 3-8 |
| 2-15 | 2-10 | Response of Little Tallahatchie River profile to upstream reservoir | |
| Associations between slope, planform, and bed material, Tanana River near Fairbanks, Alaska | | 3-16 | 3-9 |
| 2-16 | 2-11 | Red River | |
| Processes of channel slope change | | 3-17 | 3-10 |
| 2-17 | 2-12 | Specific gauge plot for Red River at Shreveport, Louisiana, over period 1982-1986 | |
| Bed forms in sand (Missouri River) | | 3-18 | 3-11 |
| 2-18 | 2-13 | Flanking of experimental bank protection on Sacramento River | |
| Response of bed forms in sand to increasing discharge | | 3-19 | 3-12 |
| 2-19 | 2-13 | Incised channel in Long Creek basin | |
| General trend of hydraulic geometry plots for channels in erodible materials | | 3-20 | 3-13 |
| 2-20 | 2-14 | Tanana River at Fairbanks showing in-river levee and groins | |
| Generalized equilibrium concept for long-term formation and response of erodible channels | | 3-21 | 3-14 |
| 2-21 | 2-14 | Side bar deposition and sub-meandering in straight channel | |
| Width-discharge plot for specific local set of channels | | 3-22 | 3-14 |
| 2-22 | 2-16 | Sediment transport associated with shifting of meander bends | |
| Example of complex profile response to channelization | | | |
| 2-23 | 2-17 | | |
| Channel evolution model for incised channels | | | |
| 2-24 | 2-18 | | |
| Slope-discharge chart distinguishing braided from non-braided channels | | | |
| 2-25 | 2-18 | | |
| Classification of stream sediment loads | | | |
| 2-26 | 2-19 | | |
| Bed material grain size distributions and correlation with slope (Tanana River near Fairbanks, Alaska) | | | |
| 2-27 | 2-20 | | |
| Ice effects on banks of northern rivers | | | |

| Figure | Page | Figure | Page |
|--------|--|--------|------|
| 3-23 | Effect of storage reservoir on down-stream flow-duration curve | 3-16 | |
| 3-24 | Effect of storage reservoir on down-stream sediment transport (Missouri River average annual suspended sediment load at Omaha, Nebraska) | 3-16 | |
| 3-25 | Effects of storage reservoir on profile stability | 3-16 | |
| 4-1 | Aerial photograph of meandering river illustrating channel features | 4-3 | |
| 4-2 | Comparison of modern (1986) and presettlement (1830) channel locations, Fannegusha Creek, Mississippi | 4-4 | |
| 4-3 | Major sediment source: valley landslide | 4-5 | |
| 4-4 | Tributary gully | 4-5 | |
| 4-5 | Stratification of bank soils | 4-6 | |
| 4-6 | Bank failure | 4-6 | |
| 4-7 | Piping and seepage in bank | 4-6 | |
| 4-8 | Nick zone in degrading channel (clay layer) | 4-7 | |
| 4-9 | Channel bar with various sediment classes and debris | 4-7 | |
| 4-10 | Mouth of perched tributary | 4-7 | |
| 4-11 | Exposed bridge piling | 4-7 | |
| 4-12 | Flood stain marks on piers | 4-7 | |
| 4-13 | Example survey cross section | 4-8 | |
| 4-14 | Example of stream profile | 4-9 | |
| 4-15 | Grid photograph of coarse sediment and comparison of analysis methods | 4-10 | |
| 5-1 | Example of allowable velocity data with provision for sediment transport | 5-2 | |
| 5-2 | Boundary shear stress in uniform flow | 5-3 | |
| 5-3 | Shields diagram: dimensionless critical shear stress | 5-4 | |
| 5-4 | Example of allowable shear stresses (“tractive forces”) for cohesive materials | 5-4 | |
| 5-5 | Example of allowable velocity-depth data for granular materials | 5-5 | |
| 5-6 | Insufficiency of allowable velocity or shear stress criterion for stability of alluvial channel | 5-6 | |
| 5-7 | Velocities and depths in compound cross section | 5-6 | |
| 5-8 | Roughness changes in a large sand bed river during floods | 5-6 | |
| 5-9 | Tentative guide to width-discharge relationships for erodible channels | 5-8 | |
| 5-10 | Tentative guide to depth-discharge relationships for erodible channels | 5-9 | |
| 5-11 | Tentative guide to slope-discharge relationships for erodible channels | 5-10 | |
| 5-12 | Infilling of oversized flood control channel by deposition of sand in floods | 5-11 | |
| 5-13 | Comparison of computed and measured bed load in Tanana River near Fairbanks, Alaska | 5-12 | |
| 5-14 | Mechanism of bank failure by internal erosion | 5-14 | |
| 5-15 | Stability analysis for steep cohesive river banks | 5-15 | |
| 5-16 | Meander geometry | 5-15 | |
| 5-17 | Suggested relationship between bankfull (channel-forming) discharge and meander wavelength for layout of new channel | 5-16 | |
| 5-18 | Distortion of meander pattern upstream of protected length | 5-16 | |
| 6-1 | Regulated river with levees on meandering alignment | 6-3 | |
| 6-2 | Construction of a meandering alignment | 6-4 | |
| 6-3 | Alignment modifications to eroding bends | 6-5 | |
| 6-4 | Alternative levee locations along braided channel | 6-5 | |
| 6-5 | Perched channel on aggrading alluvial fan | 6-5 | |
| 6-6 | Principal active source of fan bed load may be downstream of apex | 6-5 | |
| 6-7 | Cross-slope interceptor channels collecting flood flows from adjacent alluvial fans | 6-6 | |
| 6-8 | Use of grade controls to limit profile degradation and downstream sedimentation | 6-7 | |
| 6-9 | Use of stepped sill on grade control structure to match upstream rating curve | 6-7 | |
| 6-10 | Classification of grade control structures | 6-7 | |
| 6-11 | Sheet pile weir stabilizer | 6-9 | |
| 6-12 | Flume-type grade control/gauging structure | 6-10 | |
| 6-13 | Drop structure with energy dissipator | 6-10 | |

| Figure | Page | Figure | Page |
|--------|------|--------|------|
| 6-14 | 6-10 | B-2 | B-4 |
| 6-15 | 6-11 | B-3 | B-5 |
| 6-16 | 6-12 | C-1 | C-4 |
| 6-17 | 6-12 | C-2 | C-6 |
| 6-18 | 6-12 | C-3 | C-9 |
| 6-19 | 6-12 | | |
| 6-20 | 6-13 | | |
| 6-21 | 6-14 | | |
| 6-22 | 6-14 | | |
| 6-23 | 6-15 | | |
| 6-24 | 6-15 | | |
| B-1 | B-3 | | |