

TECHNICAL MANUAL
No. 5--813-8

HEADQUARTERS
DEPARTMENT OF THE ARMY
WASHINGTON, D.C. 15 September 1986

WATER DESALINATION

| | | Paragraph | Page |
|------------|---|-----------|------|
| CHAPTER 1. | GENERAL | | |
| | Purpose | 1-1 | 1-1 |
| | General design considerations | 1-2 | 1-1 |
| | Special design considerations | 1-3 | 1-1 |
| | Economic considerations | 1-4 | 1-1 |
| | Appendices | 1-5 | 1-1 |
| CHAPTER 2. | SITE SELECTION | | |
| | Site technical requirements | 2-1 | 2-1 |
| | Water storage and system modularization | 2-2 | 2-1 |
| CHAPTER 3. | WATER SOURCE SELECTION | | |
| | General..... | 3-1 | 3-1 |
| | Quality | 3-2 | 3-1 |
| | Selection versus rejection of potential raw water sources | 3-3 | 3-1 |
| CHAPTER 4. | PROCESS SELECTION | | |
| | General process selection..... | 4-1 | 4-1 |
| | Process limitations..... | 4-2 | 4-2 |
| | Distillation/condensation energy..... | 4-3 | 4-3 |
| | Membrane energy..... | 4-4 | 4-5 |
| | Waste disposal | 4-5 | 4-5 |
| | Preliminary process selection..... | 4-6 | 4-5 |
| | Process selection..... | 4-7 | 4-5 |
| CHAPTER 5. | PRETREATMENT CONSIDERATIONS | | |
| | General..... | 5-1 | 5-1 |
| | Chemical treatment..... | 5-2 | 5-1 |
| | Degasification and deaeration..... | 5-3 | 5-5 |
| | Filtration with granular media..... | 5-4 | 5-5 |
| | Secondary filtration | 5-5 | 5-5 |
| | Disinfection | 5-6 | 5-6 |
| CHAPTER 6 | DISTILLATION/CONDENSATION TECHNIQUES | | |
| | General..... | 6-1 | 6-1 |
| | High-temperature distillation | 6-2 | 6-1 |
| | Low-temperature distillation | 6-3 | 6-1 |
| | Mechanical distillation..... | 6-4 | 6-1 |
| | Thermal discharge | 6-5 | 6-7 |
| | Design analysis..... | 6-6 | 6-7 |
| | Materials of construction | 6-7 | 6-7 |
| | Distillation/condensation system design | 6-8 | 6-7 |
| CHAPTER 7. | MEMBRANE TECHNIQUES | | |
| | Electrodialysis..... | 7-1 | 7-1 |
| | Electrodialysis-reversal design | 7-2 | 7-1 |
| | Reverse osmosis | 7-3 | 7-3 |
| | Reverse osmosis membrane staging configurations..... | 7-4 | 7-7 |
| | Reverse osmosis system design | 7-5 | 7-11 |
| | Materials of construction | 7-6 | 7-13 |
| CHAPTER 8. | ION EXCHANGE | | |
| | General..... | 8-1 | 8-1 |
| | Pretreatment..... | 8-2 | 8-1 |
| | Desalination | 8-3 | 8-2 |
| | Demineralization..... | 8-4 | 8-5 |

| | | |
|--------------|---|----------|
| CHAPTER 9. | POST-TREATMENT | |
| | General..... | 9-1 |
| | Remineralization and aeration | 9-2 |
| | Post-treatment of distilled water | 9-3 |
| | Post-treatment of reverse osmosis product water | 9-4 |
| | Post-treatment of electrodialysis-reversal product water..... | 9-5 |
| CHAPTER 10. | WASTE DISPOSAL | |
| | General..... | 10-1 |
| | Pretreatment wastes | 10-2 |
| | Distillation/condensation system wastes | 10-3 |
| | Membrane system wastes | 10-4 |
| | Ion-exchange system wastes | 10-5 |
| | Ultimate disposal | 10-6 |
| APPENDIX A. | SAMPLE PROBLEMS | A-1 |
| APPENDIX B. | WATER TESTING REQUIRED FOR DESALINATION TREATMENT | B-1 |
| APPENDIX C. | REFERENCES | C-1 |
| BIBLIOGRAPHY | | Biblio-1 |

LIST OF FIGURES

| | | |
|--------|------|---|
| FIGURE | 2-1 | Typical Desalination Flowsheet |
| | 2-2 | Typical Reverse Osmosis Desalination System |
| | 4-1 | Energy Consumption |
| | 5-1 | Pretreatment Techniques |
| | 5-2 | Approximate Concentration Factor Limits for Calcium Sulfate in Sea Water |
| | 5-3 | Disinfection Alternatives |
| | 6-1 | Three Methods of Vaporization |
| | 6-2 | Multiple-Effect Vertical-Tube Evaporation Process |
| | 6-3 | Multistage Flash Distillation Facility |
| | 6-4 | Waste Heat Recovery Evaporation Process |
| | 6-5 | Vapor-Compression Vertical-Tube Distillation System |
| | 7-1 | Principles of Electrodialysis Desalination |
| | 7-2 | Reverse Osmosis Principles |
| | 7-3 | Reverse Osmosis Desalination System |
| | 7-4 | Flow-Work Exchanger Principles |
| | 7-5 | Construction of a Tubular Reverse Osmosis Membrane |
| | 7-6 | Internal Construction of a Spiral-Wound Membrane |
| | 7-7 | Internal Construction of a Hollow Fine-Fiber Reverse Osmosis Membrane Module |
| | 7-8 | Reverse Osmosis Product Staging |
| | 7-9 | Reverse Osmosis Membrane Reject Staging |
| | 8-1 | Principles of Ion-Exchange Processes |
| | 8-2 | RDI Process |
| | 8-3 | Three-Unit Variation Desal Process |
| | 8-4 | Two-Unit Variation Desal Process |
| | 8-5 | Demineralization Two-Bed Flowsheet |
| | 9-1 | Break-Point Chlorination Curve |
| | 10-1 | Waste Disposal Overview |
| | 10-2 | Pretreatment Sludge Disposal |
| | 10-3 | Deep-Well Disposal Unit |
| | 10-4 | Brine Waste Disposal |
| | A-1 | Sample Use of Table 4-1 |
| | A-2 | Sample Use of Table 4-2 |
| | A-3 | Water Analysis (Sample Problem A-1a) |
| | A-4 | Sample Use of Table 4-3 |
| | A-5 | Water Analysis (Sample Problem A-1b) |
| | A-6 | Water Analysis (Sample Problem A-1c) |
| | A-7 | Low-Pressure Reverse Osmosis System |
| | A-8 | Sample Use of Table 4-1 |
| | A-9 | Water Analysis (Sample Problem A-2) |
| | A-10 | Sample Use of Table 4-2 |
| | A-11 | Sample Use of Table 4-3 |
| | A-12 | Plan View of Vapor Compression System |
| | A-13 | Water Analysis (Sample Problem A-4) |
| | A-14 | Amberlite IR-120 Plus Leakage Data Regeneration-5 lbs. H ₂ SO ₄ (66° Be)/cu. ft. |
| | A-15 | Amberlite IR-120 Plus Iso-Capacity Data Regeneration-5 lbs. H ₂ SO ₄ (66° Be)/cu. ft. |
| | A-16 | Amberlite IR-120 Plus Capacity Correction for Alkalinity |
| | A-17 | Amberlite IR-120 Plus Leakage Data Regeneration-3 lbs. H ₂ SO ₄ (66° Be)/cu. ft. |
| | A-18 | Amberlite IR-120 Plus Iso-Capacity Data Regeneration-3 lbs. H ₂ SO ₄ (66° Be)/cu. ft. |
| | A-19 | Amberlite IR-120 Plus Capacity Correction for Alkalinity |
| | A-20 | Cation Exchangers Plan |
| | A-21 | Degasifier and Clearwell Plan |

FIGURE A-22 Three Projections of the Water Blends That Satisfy TB MED 576 Requirements
A-23 Plan View of a Two-Pass Reverse Osmosis System

LIST OF TABLES

| | | |
|-------|-----|--|
| Table | 4-1 | Preliminary Desalination Process Selection |
| | 4-2 | Selecting Desalination Processes after Water Quality Data are Obtained |
| | 4-3 | Final Selection of a Desalination Technique from Treatability Data |
| | 5-1 | The Maximum Allowable Contaminants in the Feed Water Used by Various Desalination Processes |
| | A-1 | Water Constituents at Treatment Stages with 5 Pounds/Cubic Foot Acid Regeneration |
| | A-2 | Water Constituents at Treatment Stages with 3 Pounds/Cubic Foot Sulfuric Acid Regeneration |
| | A-3 | Cost Projections for Possible Optimum Blends |