

Technical Manual
No. 5-820-4
Air Force Manual
No. 88-5, Chapter 4

HEADQUARTERS
DEPARTMENTS OF THE ARMY
AND THE AIR FORCE
Washington, D.C. 14 October 1983

DRAINAGE FOR AREAS OTHER THAN AIRFIELDS

	Paragraph	Page
CHAPTER 1. INTRODUCTION		
Purpose and scope.....	1-1	1-1
General investigations.....	1-2	1-1
Environmental considerations.....	1-3	1-1
2. HYDROLOGY		
General.....	2-1	2-1
Design storm.....	2-2	2-1
Infiltration and other losses.....	2-2	2-1
Runoff computations.....	2-4	2-2
3. HYDRAULICS		
General.....	3-1	3-1
Channels.....	3-2	3-1
Bridges.....	3-3	3-4
Curb-and-gutter sections.....	3-4	3-5
Culverts.....	3-5	3-5
Underground hydraulic design.....	3-6	3-9
Inlets.....	3-7	3-9
Vehicular safety and hydraulically efficient drainage practice.....	3-8	3-17
4. HYDRAULIC STRUCTURES		
Manholes and junction boxes.....	4-1	4-1
Detention pond storage.....	4-2	4-1
Outlet energy dissipators.....	4-3	4-1
Drop structures and check dams.....	4-4	4-5
Miscellaneous structures.....	4-5	4-5
5. EROSION CONTROL AND RIPRAP PROTECTION		
General.....	5-1	5-1
Riprap protection.....	5-2	5-1
Selection of stone size.....	5-3	5-1
Riprap gradation.....	5-4	5-2
Riprap design.....	5-5	5-2
6. SUBSURFACE DRAINAGE		
General.....	6-1	6-1
Subsurface drainage requirements.....	6-2	6-1
Laboratory tests.....	6-3	6-1
Flow of water through soils.....	6-4	6-1
Drainage of water from soil.....	6-5	6-2
Backfill for subsurface drains.....	6-6	6-2
APPENDIX A. REFERENCES		A-1
B. HYDRAULIC DESIGN DATA FOR CULVERTS		B-1
C. PIPE STRENGTH, COVER AND BEDDING		C-1
D. NOTATION		D-1
E. BIBLIOGRAPHY		E-1

LIST OF FIGURES

	Page
Figure 3-1 Superelevation formulas.....	3-3
3-2 Nomograph for flow in triangular channels.....	3-6
3-3 Capacity of grate inlet in sump water pond on grate.....	3-11
3-4 Capacity of curb opening inlet at low point in grade.....	3-12
3-5 Standard type "A" and type "B" inlets.....	3-14
3-6 Type "C" inlet—square grating.....	3-15
3-7 Standard type "D" inlet.....	3-16
4-1 Standard storm drain manhole.....	4-2
4-2 Standard precast manholes.....	4-3
4-3 Junction details for large pipes.....	4-4
4-4 Outlet security barrier.....	4-6
B-1 Inlet control.....	B-2
B-2 Headwater depth for concrete pipe culverts with inlet control.....	B-3
B-3 Headwater depth for oval concrete pipe culverts long axis vertical with inlet control.....	B-4
B-4 Headwater depth for oval concrete pipe culverts long axis horizontal with inlet control.....	B-5

	<i>Page</i>
Figure No.	
B-5 Headwater depth for corrugated metal pipe culverts with inlet control.....	B-6
B-6 Headwater depth for structural plate and standard corrugated metal pipe-arch culverts with inlet control.....	B-7
B-7 Headwater depth for box culverts with inlet control.....	B-8
B-8 Headwater depth for corrugated metal pipe culverts with tapered inlet-inlet control.....	B-9
B-9 Headwater depth for circular pipe culverts with beveled ring inlet control.....	B-10
B-10 Outlet control.....	B-11
B-11 Head for circular pipe culverts flowing full, $n = 0.012$	B-13
B-12 Head for oval circular pipe culverts long axis horizontal or vertical flowing full, $n = 0.012$	B-14
B-13 Head for circular pipe culverts flowing full, $n = 0.024$	B-15
B-14 Head for circular pipe culverts flowing full, $n = 0.0328$ to 0.0302	B-16
B-15 Head for standard corrugated metal pipe-arch culverts flowing full, $n = 0.024$	B-17
B-16 Head for field-bolted structural plate pipe-arch culverts 18 in. corner radius flowing full, $n = 0.0327$ to 0.0306	B-18
B-17 Head for concrete box culverts flowing full, $n = 0.012$	B-19
B-18 Tailwater elevation at or above top of culvert.....	B-21
B-19 Tailwater below the top of the culvert.....	B-22
B-20 Circular pipe—critical depth.....	B-24
B-21 Oval concrete pipe long axis horizontal critical depth.....	B-25
B-22 Oval concrete pipe long axis vertical critical depth.....	B-26
B-23 Standard corrugated metal pipe-arch critical depth.....	B-27
B-24 Structural plate pipe-arch critical depth.....	B-28
B-25 Critical depth rectangular section.....	B-29
B-26 Culvert capacity circular concrete pipe groove-edged entrance 18" to 66".....	B-32
B-27 Culvert capacity circular concrete pipe groove-edged entrance 60" to 180".....	B-33
B-28 Culvert capacity standard circular corrugations metal pipe projecting entrance 18" to 36".....	B-34
B-29 Culvert capacity standard circular corrugations metal projecting entrance 36" to 66".....	B-35
B-30 Culvert capacity standard circular corrugations metal headwall entrance 18" to 36".....	B-36
B-31 Culvert capacity standard circular corrugations metal headwall entrance 36" to 66".....	B-37
B-32 Culvert capacity standard corrugations metal pipe-arch projecting entrance 25" x 16" to 43" x 27".....	B-38
B-33 Culvert capacity standard corrugations metal pipe-arch projecting entrance 50" x 31" to 72" x 44".....	B-39
B-34 Culvert capacity standard corrugations metal pipe-arch headwall entrance 25" x 16" to 43" x 27".....	B-40
B-35 Culvert capacity standard corrugations metal pipe-arch headwall entrance 50" x 31" to 72" x 44".....	B-41
B-36 Culvert capacity square concrete box 90° and 15° wingwall flare 1.5' x 1.5' to 7' x 7'.....	B-42
B-37 Culvert capacity square concrete box 30° to 75° wingwall flare 1.5' x 1.5' to 7' x 7'.....	B-43
B-38 Culvert capacity rectangular concrete box 90° and 15° wingwall flare 1.5', 2.0' and 2.5' heights.....	B-44
B-39 Culvert capacity rectangular concrete box 90° and 15° wingwall flare 3' and 4' heights.....	B-45
B-40 Culvert capacity rectangular concrete box 90° and 15° wingwall flare 5' and 6' heights.....	B-46
B-41 Culvert capacity rectangular concrete box 30° to 75° wingwall flare 1.5', 2.0' and 2.5' heights.....	B-47
B-42 Culvert capacity rectangular concrete box 30° to 75° wingwall flare 3' and 4' heights.....	B-48
B-43 Culvert capacity rectangular concrete box 30° to 75° wingwall flare 5' and 6' heights.....	B-49
C-1 Three main classes of conduits.....	C-8
C-2 Free-body conduit diagrams.....	C-9
■ C-3 Embankment beddings circular pipe	C-10
■ C-4 Trench beddings for circular pipe.....	C-11
■ C-5 Flexible pipe bedding and installation.....	C-12
■ C-6 Beddings for positive projecting conduits.....	C-12a

LIST OF TABLES

<u>Table</u>	<i>Page</i>
2-1 Typical Values of Infiltration Rates.....	2-2
4-1 Maximum Permissible Mean Velocities to Prevent Scour.....	4-1
B-1 Entrance Loss Coefficients	B-12
B-2 Manning's n for Natural Stream Channels.....	B-20
B-3 Roughness Coefficients for Various Pipes.....	B-31
C-1 Suggested Maximum Cover Requirements for Asbestos-Cement Pipe.....	C-2
C-2 Suggested Maximum Cover Requirements for Concrete Pipe.....	C-3
C-3 Suggested Maximum Cover Requirements for Corrugated-Aluminum-Alloy Pipe, Riveted, Helical, or Welded Fabrication, 2 $\frac{1}{4}$ Inch Spacing, $\frac{1}{2}$ -Inch Deep Corrugations.....	C-4
C-4 Suggested Maximum Cover Requirements for Corrugated-Steel-Pipe, 2 $\frac{1}{4}$ Inch Spacing, $\frac{1}{2}$ -Inch Deep Corrugations.....	C-5
C-5 Suggested Maximum Cover Requirements for Structural-Plate-Aluminum-Alloy Pipe, 9-Inch Spacing, 2 $\frac{1}{2}$ -Inch Corrugations.....	C-6
C-6 Suggested Maximum Cover Requirements for Corrugated Steel Pipe, 125 mm Span, 25 mm Corrugations.....	C-7
C-7 Suggested Maximum Cover Requirements for Structural Plate Steel Pipe, 6-Inch Span, 2-Inch Deep Corrugations.....	C-13
C-8 Suggested Maximum Cover Requirements for Corrugated Steel Pipe, 3-Inch Span, 1-Inch Corrugations.....	C-14
C-9 Suggested Guidelines for Minimum Cover.....	C-16