

SURFACE DRAINAGE FACILITIES FOR AIRFIELDS AND HELIPORTS

| | Paragraph | Page |
|--------------------------------------------------------------------|-----------|----------|
| Purpose and scope | 1 | 3 |
| Design objectives for airfield and heliport surface drainage | 2 | 3 |
| Drainage protection required..... | 3 | 3 |
| Hydrologic considerations | 4 | 3 |
| Rainfall | 5 | 4 |
| infiltration | 6 | 4 |
| Rate of supply | 7 | 7 |
| Runoff | 8 | 7 |
| Storage | 9 | 9 |
| Design procedures for the drainage system | 10 | 9 |
| APPENDIX A: preferences | | A-1 |
| B: Design procedure | | B-1 |
| C: Design example | | C-1 |
| BIBLIOGRAPHY | | Biblio-1 |

LIST OF FIGURES

| | |
|-----------------------------------------------------------------------------------------------------------------------------------------------------------|------|
| Figure 1. Design storm index: 1-hour rainfall intensity-frequency data for continental United States excluding Alaska. | 5 |
| 2. Standard rainfall intensity-duration curves or standard supply curves. | 6 |
| 3. Rates of runoff and rates of supply corresponding to standard supply curves No. 2.0 and 2.2; n = 0.40 and S = 1 percent. | 8 |
| B-1. Diagram for estimating 2-year 1-hour rainfall. | B-2 |
| B-2. Rates of runoff versus duration of supply for turfed areas; L = 20, 40, 60, 80, 100, and 125 feet. | B-4 |
| B-3. Rates of runoff versus duration of supply for turfed areas; L = 150, 200, 250, 300, 400, 500, and 600 feet. | B-5 |
| B-4. Rates of runoff versus duration of supply for turfed areas; L = 800, 1,000, and 1,200 feet. | B-6 |
| B-5. Computation of hydrograph to represent runoff from a supply of specified duration. | B-7 |
| B-6. Modification in L required to compensate for differences in n and S. | B-8 |
| B-7. Rates of runoff corresponding to supply curves No. 0.4 and 0.6; n = 0.40 and S = 1 percent. | B-10 |
| B-8. Rates of runoff corresponding to supply curves No. 0.8 and 1.0; n = 0.40 and S = 1 percent. | B-11 |
| B-9. Rates of runoff corresponding to supply curves No. 1.2 and 1.4; n = 0.40 and S = 1 percent. | B-12 |
| B-10. Rates of runoff corresponding to supply curves No. 1.6 and 1.8; n = 0.40 and S = 1 percent. | B-13 |
| B-11. Rates of runoff corresponding to supply curves No. 2.0 and 2.2; n = 0.40 and S = 1 percent. | B-14 |
| B-12. Rates of runoff corresponding to supply curves No. 2.4 and 2.6; n = 0.40 and S = 1 percent. | B-15 |
| B-13. Rates of runoff corresponding to standard supply curves No. 2.8 and 3.0; n = 0.40, S = 1 percent. | B-16 |
| B-14. Rates of runoff corresponding to standard supply curves No. 3.2 and 3.4; n = 0.40, S = 1 percent. | B-17 |
| B-15. Consolidated design curve composite of peak runoff rates and critical durations of supply shown in figures B-7 through B-14. | B-19 |
| B-16. Sample computations of storage required with selected drain-inlet capacity to provide for runoff from an acre of turf under assumptions designated. | B-21 |
| B-17. Drain-inlet capacity versus maximum surface storage; L = 0 and 40 feet. | B-23 |
| B-18. Drain-inlet capacity versus maximum surface storage; L = 100 and 200 feet. | B-24 |
| B-19. Drain-inlet capacity versus maximum surface storage; L = 300 and 400 feet. | B-25 |
| B-20. Drain-inlet capacity versus maximum surface storage; L = 600 and 800 feet. | B-26 |
| B-21. Drain-inlet capacity versus maximum surface storage; L = 1,000 and 1,200 feet. | B-27 |
| B-22. Nomograph for computing required size of circular drain smooth interior, flowing full; n = 0.012. | B-29 |
| B-23. Nomograph for computing required size of circular standard corrugated metal pipe, 25 percent paved invert, flowing full; n = 0.021. | B-30 |
| B-24. Nomograph for computing required size of circular standard corrugated metal pipe, unpaved, flowing full; n = 0.024. | B-31 |
| B-25. Nomograph for computing required size of circular structural plate pipe, unpaved, flowing full; n = 0.033. | B-32 |
| C-1. Sample computations of layout of primary storm drainage system. | C-2 |

***This manual supersedes TM 5-820-1/AFM 88-5, Chap. 1, dated April 1977.**

LIST OF TABLES

| | Page |
|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------|
| Table 1. Infiltration rate for generalized soil classifications (uncompacted). | 7 |
| B-1. Approximate intensity-frequency values. | B-1 |
| B-2. Coefficients of roughness for overland flow. | B-9 |
| B-3. Rates of runoff corresponding to intensities and durations of supply represented by standard supply curve No. 2.0 in figure 2 (n = 0.40, S = 1 percent). | B-18 |
| B-4. Design example. | B-22 |
| C-1. Airfield drainage drain-inlet capacities required to limit ponding to permissible volumes with drainage section on east side of airfield and with supply curves No. 2.0 for paved areas and 1.5 for turfed areas. | C-3 |
| C-2. Airfield drainage size and profile of underground storm drains with drainage section on east side of airfield and with supply curves No. 2.0 for paved areas and 1.5 for turfed areas. | C-7 |
| C-3. Hydraulic design data on underground storm drains where ponding is permissible. | C-12 |
| C-4. Airfield drainage drain-inlet capacities required to limit ponding to permissible volumes with drainage section in which no ponding of runoff is assumed and with supply curves No. 2.0 for paved areas and 1.5 for turfed areas. | C-15 |
| C-5. Airfield drainage size and profile of underground storm drains with drainage section in which no ponding of runoff is assumed and with supply curves No. 2.0 for paved areas and 1.5 for turfed areas. | C-17 |
| C-6. Hydraulic design data on underground storm drains where ponding is not acceptable. | C-19 |