INDEX

A	Paragraph
Abrasion	1.4.4.1
Of coatings by high wind velocity . . .	5.2.3.4
Repainting coatings subject to	5.1.6.3
Abrasion-resistant finishes	10.2.2.1
Abrasive blasting. See Blast cleaning.	
Abrasive blasting helmets	3.1.2.3
Abrasive, effect of . . .	4.4.2.5
Abrasive materials, finishes which resist	10.2.1.1, 10.2.2.4
Acid cleaning	4.4.3.4
Concrete and masonry	4.4.3.4b
Dermatitis	3.4.1.2
Hazards	3.1.1.2
Iron and steel	4.4.3.4a
Safety measures . . .	3.1.2.5
Acoustic tile coatings ..	10.2.4.1
Adhesion:	
Effect of incompatible preservatives and paints	5.2.4.2
Effect of insufficient dry between coats .	5.2.6.5
Effect of surface contaminants	4.4.1
To chalked paints . .	5.1.2.2
Use of conditioners to improve	4.4.5
Use of phosphate treatments to improve . . .	4.4.4.1, 4.4.4.2
Use of wash primers to improve	4.4.4.3
Administration areas, odorless paints for .	10.2.2.9
Advantages of programmed painting	2.1.2.4
Air conditioning equip ment, painting of . .	10.2.3.1
Air, effect of, on deterioration of exterior coatings . .	5.1.5.1
Airfield landing mats, coatings for	10.2.3.2
Airfield pavement marking	11.2.5

	Paragraph
Air regulator, use of, in spray application	4.6.5.2
Airless spray	4.6.5.1
Alkali:	
In concrete, mortar, stucco and plaster	5.2.2.3
Paints sensitive to	
Alkyds	6.2.2
Oil	6.2.3
Alkali Cleaning	4.4.3.2
Dermatitis	3.4.1.3
Use	4.4.3.2
Alligatoring	5.2.4.2
Caused by insuffient cleaning	5.2.6.1
Aluminum:	
Avoid acid cleaners .	4.4.3.4
Avoid alkaline cleaners	4.4.3.2
Characteristics . . .	5.2.2.2
Use of wash primers ..	4.4.4.3
Aluminum mixing varnish .	6.3.3.2
Aluminum paints	6.2.1, 6.3.5
Heat resistant	10.2.2.6
Oleoresinous	6.2.10
Preparations of, for use	7.4.2.2
Phenolic	6.2.11
Rubber-base	6.2.13
Use of, to prevent bleeding on treated wood	8.4.1.2
Use of, to prevent blistering	5.2.7.2
Aluminum paste ...	6.2.10, 6.3.3.2, 6.3.5.2, 7.4.2.2
Aluminum silicate	6.3.4.1
Amines, toxicity	3.4.1.2
Anti-corrosive pigments in primers for iron and steel	8.2.4.3
Anti-corrosive primers	6.3.4.2, 8.2.4.3
Anti-sweat coatings:	
Purpose	10.2.2.2
Application	10.3.2.1
Appearance changes . . .	2.2.5
Of exterior paints ...	5.1.2.1
Of interior paints ...	5.1.3.1

Paragraph

Appearance of
coatings 1.2.5, 2.2.4
Effect of application
method on 4.6.1.4
Appearance, testing . . . 4.2.2.2
Application of paint,
effect of:
Environment 4.6.1.1
Excessive, an abnormal
deterioration.... 5.2.6.4
Insufficient, an abnor
mal deterioration 5.2.6.3
Skill 4.6.1.5
Surface 4.6.1.2
Type of coating . 4.6.1.3
Weather 1.4.3
Application of paint,
effect of, on
appearance 4.6.1.4
Application properties,
testing 4.2.2.2
Arid areas, use of cement
paints 6.2.3
Asphalt, cause of
alligatoring on . . . 5.2.4.2'
Atmospheric contamination 5.2.3.2
Atomizing pressures . . . 4.6.5.2

B

Basic Lead--silico--
chromate 8.2.4.3
Bead glazing 4.5.5.4
Benzol (benzene),
toxicity 3.4.1.1
Binders, paint 6.2.1
Toxicity 3.4.1.1
Bituminous finishes . . . 10.2.2.3
Cause of alligatoring
on 5.2.4.2
Bituminous impregnated sur-
faces, coatings for . 10.2.4.2
Blast cleaning:
Classes 4.4.2.7
Degrees 4.4.2.4
Hazards 3.1.1.2
Precautions 4.4.2.6
Procedures 4.4.2.5
Safety measures . . . 3.1.2.4

Paragraph

Blast cleaning, continued
Vacuum 4.4.2.5
Wet 4.4.2.5
See also Water Blasting.
Bleach, use of, to
to detect mildew . . . 5.2.3.1
Bleeding:
By preservatives . . . 5.2.4.1,
8.4.1.2
Use of sealers to
prevent 4.4.5
Blistering 1.4.3, 5.2.6.4e
Excessive paint
application 5.2.6.4
Faulty structural
conditions 5.2.7
Insufficient dry between
coats 5.2.6.5
Rapid temperature
changes 5.2.3.3
Blistering, painting
to prevent . . .5.2.7.2, 8.4.1.4
Bosun chair, equipment
check and use 3.2.2.1d
Boxing paints 4.3.2.2
Brass, finishes for
interior 7.1.3.2
Brick. See Concrete
and masonry.
Broadcast application of
grit in non-slip
coatings . 9.4.3.1, 10.2.2.8
Brush application 4.6.3.2
Brushes, artists .11.1.4, 11.1.5.1
Brushes, paint 4.6.3.1
Brush-off blast cleaning 4.4.2.4
After steam cleaning 4.4.3.3
Classification 4.4.2.7
Procedure 4.4.2.5
Buddy system 3.1.2.6
Bulkheads See Waterfront
bulkheads.
Bulletin colors . .11.1.4, 11.1.5.1

C

Cables, equipment check
and use 3.2.2.1e
Calcium carbonate 6.3.4.1

Paragraph

Calking compounds, on exterior surfaces application . . 4.5.2.1, 8.3.2.7, 4.5.5
Camouflage coatings . . . 10.2.2.10
Carbon tetrachloride, toxicity 3.4.1.1
Carelessness, hazards . . . 3.1.1.2, 3.1.1.3, 3.2.1
Caustic soda 4.4.3.2
Ceilings:
Brush painting 4.6.3.2
Roller painting . . . 4.6.4.2
Cement asbestos surfaces:
Surface treatment . . 8.3.2.2.1
See also Concrete and masonry.
Cement--water paint:
Preparation of, for use 7.4.2.2
Application 7.3.3.3c
Centrifugal blasting . . 4.4.2.5
Chalking 5.1.2.2
Of cement paints . . . 6.2.3
Effect of, on color retention 5.1.2.1
Resulting from atmospheric contamination 5.2.3.2
Chalking paint, tinting . 4.3.3
Use of non-, in humid and wet environments 8.1.4.4
Chalky painted surfaces:
Adhesion of latex paints 6.2.7
Repainting . . . 5.1.2.2, 5.1.6.1
Soiling 5.1.2.1
Use of conditioners 4.4.5
Channel glazing 4.5.5.4
Checking 5.1.2.2
Resulting from humidity and rainfall 5.1.5.1
Chemical treatments:
Chemical Conversion Coatings 4.4.4.4
Exterior 8.3.2.6
Interior 7.3.2.6
See also Acid cleaners; Alkaline cleaners; Pickling.
Chipping hammers 4.4.2.1

Paragraph

Coastal areas 8.1.4.3
Abnormal deterioration in 5.2.3.2
Corrosion in 5.1.5.1
Coatings, Special Purpose 10.0
General 10.1
Types of coatings used for special purposes 10.2
Surface preparation and coating application 10.3
Coating type, effect of, on application 4.6.1.3
Coding, color 1.2.4
Cold storage rooms:
Paints 10.2.3.4
Procedure for painting 10.3.2.5
Color:
After boxing 4.3.2.2
Retention in exterior finishes 5.1.2.1
Retention in interior finishes 5.1.3.1
Colors:
Effect of, on illumination 1.2.3
In floor finishes . . 9.1.3.1
Functional use 1.2.5
Guidance for selection 1.2.5
In interior paints . 7.1.3.2
For Obstructions to Flying ll.2.2.3a
Special 4.3.3
Tinting 4.3.3.1
In traffic paints . . 11.2.2.3
Use of, for safety and efficiency . . . 1.2.4
Compability of Coatings 6.3.11
Compatibility with old painted surfaces . . 5.2.4.2, 6.3.11, 7.1.3.1
Compressed board 7.1.3.1
Concrete and masonry:
Characteristics . . . 5.2.2.3
Effect of, on normal deterioration . . . 5.1.5.2
Primers for exterior 8.2.4.2
Repainting exterior . 5.1.6.1
Selection of coatings for interior 7.4.1.2
Surface treatment 7.3.2.2

Paragraph

Concrete block:
Finishes for interior 7.1.3.2
See also Concrete and masonry.
Condensation, prevention of 10.1.2
With anti-sweat coatings 10.2.2.2
Conditioners 4.4.5
Conditioning 1.1.3.3
Contaminants. See Sur face contamination; Atmospheric contamination.
Contractors 2.2.2.2
Controlled chalking . . . 5.1.2.2
Conversion treatments 1.1.3.3, 4.4.4
Cooking, moisture from . 5.2.7.2
Cooling equipment, painting 10.2.3.1
Copper:
Characteristics . . . 5.2.2.2
Finishes for interior . . 7.1.3.2
Copper naphthenate, cause of abnormal deterioration . . . 5.2.4.1
Corrosion:
In coastal areas . . . 5.1.5.1
Resistance of epoxy paints 6.2.4
Resistance of vinyl paints 6.2.17
Corrosive environments . 8.1.4.5
Costs, painting 2.1.2.3
Example 2.1.2.4
Cracking of coatings 2.1.1, 5.1.2.2
Due to excessive paint application 5.2.6.4
Due to humidity and rainfall 5.1.5.1
During exterior exposure 5.1.2.2
During interior exposure 5.1.3.2
Crawl spaces, importance of, in abnormal deterioration of coating 5.2.7.1

Paragraph

Crawling 5.2.4.2
Due to insufficient cleaning 5.2.6.1
Creosote, effect of, on, abnormal deterioration 5.2.4.1
Creosote impregnated surfaces, coatings for . 10.2.4.2
Crew, in-house 2.2.2.2
Crumbling of coatings . . 5.1.2.3b
Cure of paints:
Effect of improper, on, abnormal deterioration 5.2.2.3
Effect of improper . . 6.2.3

D

Dacron rollers 4.6.4.1
Dampness, effect of . . . 1.4.3
Dark room coatings . . . 10.2.3.5
Decorative painting . . . 1.2.5
Defective Paint Materials 4.2.4
Defense, painting for passive 10.2.2.10
Definition of terms . . . 1.1.3
Degradation:
Exterior coatings . . 5.1.2.2
Interior coatings . . 5.1.3.2
Degreasing solvent . . . 4.4.3.1
Dermatitic paint materials 3.4.1.2
Safety measures . . . 3.4.2.1
See also Skin irritants.
Detergents, use of:
Acid cleaning 4.4.3.4
Cleanup after painting 4.6.7
Steam cleaning 4.4.3.3
Deterioration of coatings 2.2.5, 5.0
Abnormal 5.2.1
Normal 5.1.1
Dirt:
Carried by winds . . . 5.2.3.4
And mildew 5.2.3.1
Pickup of, on exterior coatings 5.1.2.1
Discoloration of paints, causes of:
Bleeding 5.2.4.1
Poor construction . . 5.2.7.1

Paragraph

Disintegrated paint.
See Paint, old.
Dropcloths 4.6.1.1

E

Emulsion paints, See Latex Paints
Enamel undercoaters . . . 6.3.4.2
Enamels 6.3.4
Application 7.4.3.3
Color change of, on exterior exposure . 5.1.2.1
Flatting of, on exterior exposure . 5.1.2.1
Use of, to resist mildew 5.2.3.1
Environmental conditions 1.4.4, 2.2.4
Effect of, on normal deterioration . . . 5.1.5.1
Effect of, on paint application 4.6.1.1
Hazards 3.1.1.4
In interior painting 7.1.3.3
Safety measures . 3.1.2.2
Environments:
Abnormal exterior . . 1.4.4.3
Contaminated with industrial fumes . 8.1.4.2
Interior 1.4.4.1
Normal exterior . . . 1.4.4.2
See also Corrosive environments; Humid environments; Industrial environments; Marine environments; Rural environments.
Epoxy coatings 6.2.4
Applying two-component 7.4.3.3
Toxicity 8.4.1.1
Equipment:
Cleanup, after use . 4.6.7
Safe handling 3.1.1.3
Erosion 5.1.2.3
Due to atmospheric contamination . . . 5.2.3.2
Etching, chemical 1.1.3.3, 4.4.3.4
Ethyl silicate paints . 6.2.6
Exhaust systems 3.1.2.2
Use of, to remove moisture 5.2.7.2
Explosion hazards, precautions and prevention 3.3.2
Exposure direction, effect of, on normal deterioration 5.1.5.1
Extenders, paint 6.3.4.1. . . .
Exterior Painting, See Painting, Exterior
Exudation, resin, use of sealers to prevent . 4.4.5
Eye protection 3.1.2.4

F

Fabric, coatings for . . 10.2.4.3
Face glazing 4.5.5.3
Fading in exterior paints 5.1.2.1
Fast drying paints, application 4.6.3.2
Fences, painting 4.6.4.1
Fiberboard, use of, to fill crevices 4.5.5
Fiberglass, use of, to fill crevices 4.5.5
Field testing 4.2.2.2
Fillers, masonry . . 4.4.5.3, 6.2.3
In painting . . 7.3.2.2, 7.3.2.6
Fillers, wood 4.4.5.3
Application 7.3.2.6
Film thickness (build) . 1.3.4
Checking, when repainting 5.1.6.1
Control of, by chalking 5.1.2.2
Effect of, on checking and cracking 5.1.2.2
Effect of excessive, on paint deterioration 5.1.1
Effect of excessive thinning 4.3.5
Inspection of, during application 2.2.4
In spray application 4.6.5.1
Vinyl finishes 6.2.17
Fire fighting equipment location 3.3.2, 3.3.2.1
Fire Hazards 3.3
Flame cleaning 4.4.2.3
Storage 4.2.3.1, 4.2.3.4
Use of paint removers 4.4.3.6

Paragraph

Fire-retardant paints . 10.2.2.5
First aid 3.4.2.2
Flaking of coatings,
causes 5.1.2.3
Faulty structural
conditions 5.2.7
Insufficient cleaning 5.2.6.1
Flame cleaning 4.4.2.3
Classification 4.4.2.7
Flammable materials:
Hazards 3.1.1
Safety measures . . . 3.1.2
Flammable vapors, safety
measures for 3.1.2.5
Flash point of cleaning
solvents 4.4.3.1
See also Solvents.
Flashing, effect of improper
installation of, on
abnormal dete-
rioration .5.2.7.1, 5.2.7.3
Flat finishes:
Effect of pigment
concentration .6.2.1, 6.3.4.1
Flat paints, applying . . 7.4.3.3
Flatting (loss of gloss)
in:
Exterior paints . . . 5.1.2.1
Interior paints . . . 5.1.3.1
Flatting (Loss of gloss)
causes:
Humidity and moisture 5.2.3.1
Rapid temperature
changes 5.2.3.3
Flatting pigments .6.3.3.4, 6.3.4.1
Floor finishes 9.0
General 9.1
Types of products
available 9.2
Surface preparation and
repair 9.3
Selection, preparation
and application of
coatings 9.4
Foam, use of, to fill
crevices 4.5.5
Food storage areas, odor
less paints for . . . 10.2.2.9
Fresh air blowers 3.1.2.3
Frit-silicone paints . . 10.2.2.6
Frost, effect of 1.4.3

Paragraph

Fumes:
Corrosive 1.4.4.3
Hazards 3.1.1
Safety measures 3.1.2, 3.1.2.2,
3.4.1.1
Fungicides. See mildewcides.
Fungus. See Mildew.

G

Galvanized steel:
Characteristics . . . 5.2.2.2
Painting 8.2.4.4, 8.3.2.4
Use of wash primers . 4.4.4.3
Glare, reduction of . . . 6.3.3.4
Glass:
Painting 10.2.4.4
See also Glazing compounds.
Glaze coatings 6.2.4, 6.3.7
Glaze, concrete, removal by
acid cleaning 4.4.3.4
Glazing compounds 4.5.4
Application 4.5.5
Gloss 6.3.4.1
After boxing 4.3.2.2
Gloss, effect of, on:
Improper cure 5.2.2.3
Pigment concentra
tion 6.2.1, 6.3.4.1
Gloss, loss of:
Exterior exposure . . 5.1.2.1
Interior exposure . . 5.1.3.1
Glossary . . . . 1.1.4, Appendix A
Gloves, use of, in blast
cleaning 4.4.2.6
Goggles 3.1.2.4
Use of, in blast
cleaning 4.4.2.6
Grain raising, prevention
of . . . . . 6.3.3. -3

H

Hardboard 7.1.3.1
Heat-Resistant Coatings 10.2.2.6
Humid Environments . . . 8.1.4.4
Humidity 5.2.7

Paragraph

Humidifier, effect of . . 5.2.7.2b
Hydrogen gas in ready-mixed metallic paints . . . 6.3.5.3
Hydrogen sulfide:
Effect on abnormal deterioration . . . 5.2.3.2
In industrial environments . . . 8.1.4.2
Hypochlorite bleach, solution, for Mildew removal 10.3.2.5

I

Illumination and visibility 1.2.3
Immersed structures, bituminous finishes for 10.2.2.3
Impact cleaning tools . 4.4.2.2
Industrial environments 8.1.4.2
In-house crew 2.2.2.2
Inorganic Zinc Coatings 6.2.6
Inspection 2.2.1
Job 1.3.3
Paint deterioration . 5.1.1
Paint materials . . . 4.2.2.2
Instructions:
Adjusting spray viscosity 4.6.5.2
Mixing 4.3.2
Multi-package paints 7.4.2.2
Patching materials . 4.5.6.6
Potential hazards and precautions 3.3.2
Thinning 4.3.5
Interior painting. See Painting, Interior.
Intermediate coats, tinting 4.3.3
International Orange 11.2.2.3.2
Iron. See Steel.
Iron phosphate treatment 4.4.4.1
Issue of paints 4.2.3.2

J

Joint cement 4.5.6.3
Joints, masonry, use of calking compounds and sealants in 4.5.2

Paragraph

K

Kitchens:
Painting 7.1.1
Odorless paints . . . 10.2.2.9
Knife grade compounds . . 4.5.5.2
Knot sealers . . 4.4.5.2, 7.3.2.1, 7.3.2.6
Knots, characteristics .. 5.2.2.1

L

Label instructions. See Instructions.
Lacquers 6.3.2
Application 4.6.1.3
Fire hazard 3.3.1.3
Vinyl 6.2.17
Ladders:
Check and use 3.2.2.1
Hazards 3.1.1.3
Safety measures . . . 3.1.2.1
Latex paints 6.2.7
Lead containing paints, restrictions on use of 1.5
Lifting 5.2.4.2

M

Marine Environments . . . 8.1.4.3
Masonry fillers. See Fillers, masonry.
Mechanical surface preparation
Categories 4.4.2.7
Exterior 8.3.2.6
Interior 7.3.2.6
See also Blast cleaning; Flame cleaning; Hand cleaning; Power Tool cleaning.
Mercury-Containing Fungicides, restrictions on use of 1.6
Metal:
Characteristics . . . 5.2.2.2
Effect on normal deterioration . . . 5.1.2.2

Paragraph

Metal, continued
Selection of exterior coatings . . 8.4.1.4, 8.4.1.5
Selection of interior coatings 7.4.1.3
Surface preparation . 7.3.2.3
Metallic paints 6.2.1
See also Aluminum paints.
Methyl (wood) alcohol, toxicity 3.4.1.1
Mildew, causes:
Condensation 10.2.2.2
Faulty structural conditions 5.2.7
Humidity and moisture 5.2.3.1
Mildewcides 10.2.2.7
Mildew, removal of 10.2.2.7, 10.3.2.5
Mildew-resistant paints . 10.2.2.7
Mildewed surfaces:
Cold storage areas . 10.3.2.5
Fabrics 10.2.4.3
Showers and laundries 10.3.2.6
Swimming pools 10.3.2.9
Mill scale, removal of:
Blast cleaning 4.4.2.5
Hand cleaning 4.4.2.1
Pickling 4.4.3.5
Power tools 4.4.2.2
Moisture, effect on paint deterioration 5.2.7
Moisture content, wood . 7.4
Moisture permeable materials 8.4.1.4
Mold. See Mildew.

N

Nails, non-galvanized . 5.2.7.1
Nitric acid, pickling iron and steel 4.4.3.5
Non-Ferrous metals:
Characteristics . . . 5.2.2.2
Primers 8.2.4.4
Surface preparation . 8.3.2.4
Non-slip floor paints:
To promote safety . . 9.2.1
Types 9.4.3.1, 10.2.2.8
Non-sparking tools .3.1.3, 3.3.2.1

Paragraph

O

Oakum, use of, to fill crevices 4.5.5
Obstruction marking 11.2, Appendix D-4, Table 15
Odorless paints 10.2.2.9
Alkyd 6.2.2
Latex 6.2.7

Oil and grease removal:
Alkali cleaning . . . 4.4.3.2
Prior to acid cleaning 4.4.3.4
Prior to blast cleaning 4.4.2.6
Prior to flame cleaning 4.4.2.3
Solvent wiping 4.4.3.1
Oil-modified resins . . . 6.3.3
Oil-modified urethanes . 6.2.16.1
Oil paints:
Chalking 5.1.2.2
Color change 5.1.2.1
Fire hazard 3.3.1.2
Flatting 5.1.2.1
Lifting 5.2.4.2
Soiling (dirt collection) 5.1.2.1, 5.2.3.2
Old paint 1.4.2
See also Repainting.
Old paint removal:
Acid cleaning 4.4.3.4
Alkali cleaning . . . 4.4.3.2
Blast cleaning 4.4.2.5
Hand cleaning 4.4.2.1
Power tools 4.4.2.2
Steam cleaning 4.4.3.3
See paint and varnish removers.
Operations, painting . . 4.0
Paint shop 4.1
Paint materials . . . 4.2
Paint conditioning and mixing 4.3
Preparation of surfaces 4.4
Repair of surfaces . . 4.5
Paint application . . 4.6
Operator carelessness, hazards 3.1.1.2, 3.1.1.3

Paragraph

Overhangs:
Chalking under 5.1.2.2
Dirt collection under 5.1.2.1
Effect of omission on abnormal dete rioration 5.2.7.1
Surface preparation under 5.1.6.1
Overspray 4.6.5.1
Effect of overthinning 4.6.5.2

P

Paint and varnish removers 1.1.3.3
Dermatitis 3.4.1.3
Use 4.4.3.6, 7.3.2.5
Paint brushes 4.6.3.1
Paint brush cleaners, dermatitis 3.4.1.3
Paint compatibility . . . 6.3.11
Paint containers 4.2.3.3
Paint failure, premature 1.1.3.5
Paint inspector:
Familiarity with signs of deterioration . . . 5.1.1
Sampling 4.2.2.2
Paint, leftover 4.2.3.3
Paint materials 6.0
Defective Paint . . . 4.2.4
General 6.1
Hazards 3.1.1.1
Mixing procedures . . 4.3.2
Paint binders 6.2
Procurement 4.2.1
Sampling and testing 4.2.2
Storage 4.2.3.1, 4.2.3.4
Thinning 4.3.5
Types of paints . . . 6.3
Toxicity 3.4.1.1
Paint removers. See Paint and varnish removers.
Paint shaker 4.3.2
Paint shop 4.1
Safety precautions . 3.3.2
Use for pickling . . . 4.4.3.5
Paint solids, effect of hot spray 4.6.5.1
Paint system 6.3.4.2
Paint, useful life . . . 1.1.3.4

Paragraph

Painted surfaces, inspection 2.2.1.1
See also Repainting.
Painting, exterior . . . 8.0
General 8.1
Types of products available 8.2
Surface preparation and repair 8.3
Selection, preparation, and application of coating systems . 8.4
Painting, interior (except floors) 7.0
General 7.1
Types of products available 7.2
Surface preparation and repair 7.3
Selection, preparation, and application of coating systems . . 7.4
Painting, programmed . . 2.0
General 2.1
Procedure 2.2
Painting costs 2.1.2.3
Painting crew 2.1.2.2
Safeguarding 3.1.1.5
Painting operations. See Operations, painting.
Painting priority 2.2.2.1
Particle board 7.1.3.1
Passive defense, painting for 10.2.2.10
Patching materials .7.3.2.7, 4.5.6
Applications 4.5.6.6
See also Joint cement; Patching plaster; Plastic wood; Portland cement grout; Spackle.
Patching plaster .1.1.3.3, 4.5.6.1
7.3.2.4
Peeling 2.1.1, 5.1.2.3
Intercoat 5.2.4.2
Painting to prevent . 8.4.3.6
Prevention in floor finishes 9.4.3.2
Problems from insufficient cleaning 5.2.6.1
Pentachlorphenol 5.2.4.1

Paragraph

Personnel, relative experience required for different methods of application 4.6.1.5
Phosphate treatments . . 4.4.4.1, 4.4.4.2
Plaster and Wallboard
Effect on abnormal deterioration . . . 5.2.2.3
Painting . . . App. D-4, Table 12
Repair of Surfaces . 4.5.6
Selection of Coatings for 7.4.1.4
Surface preparation 7.3.2
Plastics, painting of 6.2.6
Pressurized equipment:
Check and use 3.2.2.1
Hazards 3.1.1
Pretreatment 1.1.3.3, 4.4.4
See also Wash primers and phosphate treatments.
Preventive maintenance
Painting 2.1.2.1
Order of priority . 2.2.2.1
Use of records . . . 2.2.8
Primers 6.3.4.2
In repainting 5.1.6.1
Mixing 8.4.2
Types 8.2.4.3
See also Wash primers.
Primer-sealers 6.3.4.2
Application 7.4.3.3
Priority in maintenance painting 2.2.2.1
Problems in spraying . . 4.6.5.3
Project preparation . . . 2.2.2
Propeller mixer 4.3.2
Protective clothing . . . 3.1.2.5
Putty 4.5.3
Use in painting .7.3.2.1, 4.5.5

R

Radiator coatings 10.2.3.8
Radioactive areas:
Abrasion-resistant finishes 10.2.2.1
Coatings 10.2.3.9

Paragraph

Rainfall:
Effect on normal deterioration . . 5.1.5.1
Heavy 8.1.4.4
Washoff of dirt . . 5.1.2.1
Rayon rollers 4.6.4.1
Ready-mixed aluminum paints 6.3.5.1
Ready-to-mix aluminum paints 6.3.5.2
Records, painting . . . . Appendix B
Project planning . . Appendix B-l
Daily project report . . . . . Appendix B-2
Performance record Appendix B-3
Historical record . Appendix B-4
Red Lead:
Primers 8.2.4.3
Toxicity 3.4.1.1
Reflectorized traffic paints 11.2.2.1, 11.2.5
Removal, paint:
Very old exterior paint 8.3.2.5
Very old interior paint 7.3.2.5
See also Old paint, removal
Repainting 5.1.6
Chalked paint 5.1.2.2
Importance of surface preparation 4.4.1
Frequency 2.2.8
Priority 2.2.2.1
Problems from high wind velocity . . . 5.2.3.4
Removal of efflorescence before 5.2.2.3
To prevent deterioration 5.1.1, 5.1.2
Repairs:
Effect of improper, on abnormal deterioration 5.2.6.2. . . .
Reservoirs. See Storage tanks
Resins hardeners, dermatitis 3.4.1.2
Resinous areas, sealing 7.3.2.1
Resinous materials, in wood 5.2.2.1

Paragraph

Resins, dermatitis . . . 3.4.1.2
Respiratory protection . 3.1.2.2, 3.1.2.3
Blast cleaning 4.4.2.6
Rigging:
Equipment check and use 3.2.2.1
Hazards 3.1.1.3
Safety measures . . . 3.1.2.1
Roller Application . . . 4.6.4
Rollers, paint, types . . 4.6.4.1
Ropes, check and use . . 4.2.2.1e
Roughness of paint, effect on soiling of exterior paints 5.1.2.1
Rubber-base paints . . . 6.3.2
Application 7.4.3.3d
Runs and sags, effect of excessive thinning ... 4.6.5.2
Rural environments . . . 8.1.4.1
Rust, effect on coatings 5.2.2.2
Rust removal:
Acid cleaning 4.4.3.4
Blast cleaning 4.4.2.5
Hand cleaning 4.4.2.1
Pickling 4.4.3.5
Power tools 4.4.2.2
Rust prevention by phosphate treatment . 4.4.4.1

S

Safety, general 3.0
Accident hazards . 3.2
Fire hazards . . . 3.3
Health hazards . . 3.4
Health services . . 3.5
Check-off list . . 3.1.3
Non-slip floors, finishes for . . 9.1.2
Use of signs . . . 11.1.1
Use of traffic paint 11.2.1
Safety helmets. See Abrasive blasting helmets; Hard hats
Sagging, due to excessive paint 5.2.6.4
Salt-laden atmosphere ... 8.1.4.3
Effect on abnormal deterioration . . . 5.2.3.2

Paragraph

Sanding 1.1.3.3
Eye protection 3.1.2.4, 4.4.2.2
Interior surfaces . . 7.3.2.1
Wood floors 9.3.2.1
Scaffolding:
Brushing technique with 4.6.3.2
Check and use 3.2.2.1
Hazards 3.1.1.3
Safety measures 3.1.2.1
Scalers:
Hand 4.4.2.1
Needle 4.4.2.2
Rotary 4.4.2.2
Scheduling of painting with respect to dete rioration 5.1.1
Scheduling of painting with respect to seasons and weather conditions . . 2.2.3.1
Scrapers 4.4.2.1, 7.3.2.6
Sealants 4.5.2.2
Application . . . 8.3.2.7, 4.5.5
Seal coating 1.1.3.3
Sealers 6.3.3.3
Seasons, effect on scheduling exterior painting 2.2.3.1
Semigloss finishes. See Gloss finishes.
Service of interior paints 7.1.3.4
Shoes, safety 3.1.2.5
Shop-coated iron and steel surface treatment . . 8.3.2.3
Shower rooms 1.4.4.1
Coatings 10.2.3.10
Moisture 5.2.7.2
Painting 7.1.1, 10.2.3.6
Signs and traffic marking 11.0
Signs 11.1
Traffic marking . . . 11.2
References and standards 11.3
Sign substrates 11.1.2
Silica 6.3.4
Silicated alkali 4.4.3.2
Silicone water repellants:
Application 8.4.3.3
Cause of crawling . . 5.2.4.2

Paragraph

Skin irritants:
Effect on health . . . 3.1.2.1
Paint materials 3.1.1.1, 3.4.1.2
Solvents 3.4.1.2
Surface preparation materials 3.1.1.2
Solvents . . . . . Appendix C
Restrictions on use of 1.7.1
Specifications . . . . . Appendix D
Products . 1.3.1, Appendix D-l
Listed by source . . Appendix D-2
Numerical List . . . Appendix D-3
Recommended coating . . . . . Appendix D-4
Spot-cleaning 4.4.2.1
Spot-Painting . . . 2.2.2.1, 2.2.2.1, 2.2.5, 2.2.8, 5.1.6.1
Spot-priming 7.3.2.3
Spray application of acid cleaners 4.4.3.4
Spray booths 4.1.2
Cleaning 4.1.3
Spray equipment:
Application 4.6.5.2
Grounding . . 3.2.2.1f, 3.3.1.1
Problems 4.6.5.3
Types 4.6.5.1
Spray gun controls . . . 4.6.5.2
Spraying:
Fire hazards 3.3.1.1
Safety measures . . . 3.1.2
Vinyl finishes 6.2.1.7
Spray room, safety measures 3.3.2
Stage, swing. See Swing Stage.
Stainless steel:
Acid cleaners, not to be used on . . . 4.4.3.4
Alkali cleaner, not to be used on . . . 4.4.3.2
Wash primers 4.4.4.3
Stains, wood
Application . . . 6.3.6, 7.4.3.4
In interior painting 6.3.6, 7.2.3
Use with wood filler . 4.4.5.3
Standpipes. See Storage tanks
Steam cleaning 4.4.3.3
Exterior surfaces . . 8.3.2.6
Hazards 3.1.1.2
Procedure 4.4.3.3

Paragraph

Steam lines, hazards . . 3.1.1.4
Steam, protection against 1.4.4.1
Steel:
Characteristics . . . 5.2.2.2, 8.4.1.5
Effect on normal deterioration . . . 5.1.5.2
Painting . . . App. D-4, Table 15
Primers 6.3.4.2, 8.2.4.3
Repainting 5.1.6.1
Shopcoated 8.3.2.3
Surface preparation . . . 8.3.2.3
Stone. See Concrete and masonry.
Storage tanks:
Coatings for fuel and oil 10.2.3.12
Coatings for water . 10.2.3.11
Painting 10.3.2.7
Stresses in paint film, cause of checking and cracking 5.1.2.2
Stucco, characteristics 5.2.2.3
Styrene-acrylate paints 6.2.13
Surface preparation . . . 4.4.1
In repainting 5.1.6.1
Surface preparation materials, hazards . 3.1.1.2
Surface repair . . . 4.5.1, 8.3.2.7
See also Operations, painting and Repairs.
Surface type, effect on paint application . . 4.6.1.2
Swimming pools:
Coatings 10.2.3.14
Painting 10.3.2.9
Swing stage, check and use 3.2.2.ld

T

Talc 6.3.4.1
Tank roof paints 10.2.2.8
Tanks, storage. See storage tanks.
Temperature changes, effect on:
Abnormal deterioration 5.2.3.3, 1.4.4.3
Checking and cracking 5.1.2.2
Normal deterioration . 5.1.5.1

Paragraph

Temperature, effect on:
Application 4.6.2, 1.4.3
Blast cleaning 4.4.2.6
Storage 4.2.3.1
Temperature, extreme . . 1.4.4.3
Effect on phosphate treatment 4.4.4.2
Textured finishes:
Application 10.3.2.4
Use 10.2.2.11
"Threshold Limit Value" . Appendix C
Tile-like coatings. See Glaze coatings.
Tinting paint. See Colors.
Tone-down painting . . . 10.2.2.10
Toxic materials
Hazards 3.1.1.1, 3.4.1.1
Safety measures 3.1.2.1, 3.4.2.1
Toxicity 3.1.1.1
Paint materials . 1.5, 3.4.1.1, 10.2.3.11
Paint removers 4.4.3.6
Safety measures . . . 3.1.2.1
Solvents 4.4.3.1
Towers, rolling, check and use 3.2.2.lc
Traffic control 11.1.1
Traffic marking. See Signs and Traffic marking.
Trim, painting 4.6.3.2
Trisodium phosphate . . . 4.4.3.2
Use for mildew removal 10.3.2.5
Tropical climates 8.1.4.4
Normal deterioration . . 5.1.5.1
Treatment of wood 8.4.1.2

W

Wallboard. See Plaster and Wallboard.
Wash primers 4.4.4.3
Waterblast cleaning . . . 4.4.4.32
Wood alcohol. See Methyl alcohol.
Wood decay due to poor construction 5.2.7.1
Wood fillers. See Fillers, wood.
Wood floors:
Surface preparation . 9.3.2.1
Wood grain, effect on cracking 5.1.2.2, 5.2.2.1

Paragraph

Wood, open grain, use of fillers 4.4.5, 4.4.5.3
Wood, treated, selection of coatings 8.4.1.2
Wrinkling:
From improper paint application 5.2.6.4
From rapid temperature changes 5.2.3.3
In painting . . . . . 7~1.3.1
Wrinkling, avoiding, when applying clear finishes 7.4.3.2
Wood:
Application of clear finishes 7.4.3.2
Characteristics . . . 5.2.2.1
Cracking of coatings 5.1.2.2
Selection of coatings for interior 7.4.1.1
Moisture content 7.3.2.1
Preparation for painting 7.3.2.1
Primers for exterior . . 8.2.4.1
Repainting 5.1.6.1
Wood, effect on normal deterioration 5.1.5.2

X

Xylene (Xylol):
Cause of lifting . . . 5.2.4.2
In rubber-base paint . 7.4.3.3

Z

Zinc chloride and phosphoric acid. See phosphoric acid and zinc chloride.
Zinc chromate:
In anti-corrosive primers 8.2.4.3
In wash primers . . . 4.4.4.3
Toxicity 3.4.1.1
Zinc dust 8.2.4.3
Zinc dust paint 6.2.6
Zinc naphthenate 5.2.4.1
Zinc oxide, use of, to prevent mildew . . 5.2.3.1, 10.2.2.7
Zinc phosphate treatment 4.4.4.1
Zinc-rich paints 8.2.4.3
Application of 8.4.3.5

☆U.S. GOVERNMENT PRINTING OFFICE: 1994 O - (22229)